


GAMA LIGERA

CARB

6 - 5 HP



	6 HP		5 HP			
	F6ABML	F6ABMS	F5ABML	F5ABMS	F5BML	F5BMS
A (mm)	717 (28.2")		717 (28.2")		717 (28.2")	
B (mm)	390 (15.4")		390 (15.4")		361 (14.2")	
C (mm)	1.177 (46.3")	1.050 (41.3")	1.177 (46.3")	1.050 (41.3")	1.156 (45.5")	1.029 (40.5")
D (mm)	508 (20.0")	381 (15")	508 (20.0")	381 (15")	508 (20.0")	381 (15")
	28 kg	27 kg	28 kg	27 kg	25.5 kg	24.5 kg
Full throttle operating range	4.500 - 5.500 rpm		4.500 - 5.500 rpm		4.500 - 5.500 rpm	
Maximum output	4.4 Kw (6 Hp) 5.000 rpm		3.6 Kw (5 Hp) 5.000 rpm		3.6 Kw (5 Hp) 5.000 rpm	
Idling speed (neutral)	1.450 - 1.550 rpm		1.450 - 1.550 rpm		1.450 - 1.550 rpm	
Engine type	OHV		OHV		OHV	
Cylinders	1		1		1	
Displacement	148 cm ³		148 cm ³		112 cm ³	
Bore per stroke	64 x 46 mm (2.52" x 1.8")		64 x 46 mm (2.52" x 1.8")		59 x 41 mm (2.32" x 1.61")	
Ignition system	CDI		CDI		TCI	
Alternator	12V 6A		12V 6A			
Control system						
Starting system						
Gear positions	F - N - R		F - N - R		F - N - R	
Gear ratio	2.15 (28/13)		2.15 (28/13)		2.15 (28/13)	
Trim & tilt system						
Maximum fuel waste	2.3 L/h		2 L/h		2 L/h	
Fuel tank capacity	1.3 L		1.3 L		1.3 L	
Engine oil capacity	0.8 L		0.8 L		0.5 L	
Gear oil capacity	195 cm ³		195 cm ³		100 cm ³	
Included STD Propeller	3-71/8" x 9"		3-71/8" x 9"		3-71/2" x 7"	



F6ABML

Standard rotation
HP
Tiller control
MANUAL start
Long Shaft
508 mm / 20"

F5ABWL

Standard rotation
HP
REMOTE control
Electrical start
Long Shaft
508 mm / 20"

F5BMS

Standard rotation
HP
Tiller control
MANUAL start
Short Shaft
381 mm / 15"

	UN.
Owner manual	1
Stopper, hang rope assy	1
Emergency handle-start rope	1
Screwdriver	1
Spark plug	1
Spark plug sleeve	1
Pin, cotter	1


INCLUDED ACCESSORIES



PROPELLERS



	D	P	REF	DESC.
5 HP	7 ^{1/4}	6	SOL3011-073-05S	OP
	7 ^{1/2}	7	PAF4-03070000	STD
6 HP	7.8	6	PAF6-03010000	STD
	7.8	7	SOL5011-078-07	OP
	7.8	8	SOL5011-018-08	OP
	7.8	9	SOL5011-078-09	OP



B	A	D	P	R	OP	STD
Blades	Tooth Spline	Diameter	Pitch	Rotation: L (left) R (Right)	Optional	Standard



OIL	REF
10W30 10W40 NMMA approved engine oil	REC10W30U3
	REC10W30U6
	REC10W40U3
	REC10W40U6
80W90 Synthetic marine transmission oil GL-5 approved	REC80W90U3
	REC80W90U6

